What is claimed is:

- 1. An output stage for a differential amplifier comprising: 1
- 2 first and second P-type input amplifiers to receive a non-inverted differential voltage
- signal and an inverted differential voltage, respectively; 3
- 4 first and second N-type input amplifiers to receive the non-inverted differential voltage
- 5 signal and the inverted differential voltage, respectively;
- 6 a first output amplifier to receive the output of the first P-type input amplifier via an N-
- 7 type load and the output of the first N-type amplifier via a P-type load; and
- 8 a second output amplifier to receive the output of the second P-type input amplifier via an
- N-type load and the output of the second N-type amplifier via a P-type load.
 - 2. The output stage of claim 1 wherein an output voltage signal is to be provided between
 - said first and second output amplifiers.

L. 244

- 3. The output stage of claim 2 wherein said first output amplifier is a P-type amplifier and
- 1 2 said second output amplifier is an N-type amplifier.
- 1 4. The output stage of claim 1 wherein said non-inverted differential voltage signal and said
- 2 inverted differential voltage signal have matched currents.
- 5. 1 An output stage for a differential amplifier comprising:
- 2 first and second P-type transistors to receive a non-inverted differential voltage and an
- 3 inverted differential voltage, respectively;

- first and second N-type transistors to receive the non-inverted differential voltage and the inverted differential voltage, respectively;
- a first output amplifier to receive the output of the first P-type transistor via an N-type load and the output of the first N-type transistor via an N-type load; and
- a second output amplifier to receive the output of the second P-type transistor via an N-type load and the output of the second N-type transistor via an N-type load.
- 1 6. The output stage of claim 5 wherein an output voltage is to be provided between said first 2 and second output amplifiers.
 - 7. The output stage of claim 6 wherein said first output amplifier is a P-type transistor and said second output amplifier is an N-type transistor.
 - 8. The output stage of claim 5 wherein said non-inverted differential voltage signal and said inverted differential voltage signal have matched currents.
- 1 9. An output stage for a differential amplifier comprising:
- first and second P-type transistors to receive a non-inverted differential voltage and an inverted differential voltage, respectively;
- first and second N-type transistors to receive the non-inverted differential voltage and the inverted differential voltage, respectively;
- first and second N-type loads coupled to said first and second P-type transistors,
 respectively;

4

5

6

7

8 first and second P-type loads coupled to said first and second N-type transistors, 9 respectively; 10 first and second intermediate transistors coupled to said first P-type transistor and said 11 first N-type transistor; 12 a first output amplifier to receive the output of the first intermediary transistor and the 13 output of the second N-type transistor; and 14 a second output amplifier to receive the output of the second intermediary transistor and 15 the output of the second P-type transistor. 10. The output stage of claim 9 wherein an output voltage is to be provided between said first and second output amplifiers. 1 4 11. The output stage of claim 10 wherein said first output amplifier is a P-type transistor and said second output amplifier is an N-type transistor.

- 12. The output stage of claim 11 wherein said first intermediary transistor is a P-type
- 2 transistor and said second intermediary transistor is an N-type transistor.
- 1 13. The output stage of claim 9 wherein each of said transistors is a metal-oxide-
- 2 semiconductor field effect transistor.
- 1 14. The output stage of claim 7 wherein said non-inverted differential voltage signal and said
- 2 inverted differential voltage signal have matched currents.

- 1 15. The output stage of claim 12 wherein said non-inverted differential voltage signal and
- 2 said inverted differential voltage signal have matched currents.